VYSEAL-PU

PU Sealants

DESCRIPTION

Polyurethane-based elastic sealants for compatible construction joints and detailing.

BENEFITS

- Flexible joint sealing
- Adhesion to suitably prepared building substrates

APPLICATIONS

- Window and door perimeters
- Facade joints
- Compatible roofing or concrete details

INSTALLATION

- Prepare joint faces.
- Install backing rod and primer where required.
- Gun evenly and tool before skin formation.
- Protect the sealant during curing.

STORAGE & SHELF LIFE

- Store in original packaging in a dry, covered area.
- Protect from moisture, direct sunlight and physical damage.
- Shelf life and storage temperature: to be confirmed for the selected grade.

DIMENSIONS & PACKAGING

Parameter	Value
Component type	To be confirmed for the selected grade
Packaging volume	To be confirmed for the selected grade
Color	To be confirmed for the selected grade
Packaging	To be agreed with the order

TECHNICAL DATA

Property	Value / status	Test method
Movement capability	To be confirmed	To be agreed
Shore A hardness	To be confirmed	To be agreed
Tensile strength	To be confirmed	To be agreed
Elongation at break	To be confirmed	To be agreed
Skin formation time	To be confirmed	To be agreed
Curing rate	To be confirmed	To be agreed
Application temperature range	To be confirmed	To be agreed

Performance values and test methods have not been supplied for these grades. Confirm the selected product specification and supporting test data before project approval.

SPECIFICATION NOTES

Confirm component type and movement capability for the selected grade before joint design and application.